



FlexilooFirst™ 15MB Jets™ Pump Module

Technical Data

Outside Dimensions (installed).....800x600x1450mm (WxDxH)
Weight.....approx.850kgs
Generic Material.....HPL/Ply/Aluminium
Standard Pump Fitted.....Jets™ 15MB CVS
Inlet.....2” Cam lock, female
Outlet.....1¼” Cam lock, male
Electrical Connection.....230VAC 16A
Controller.....VTS CVS 110-240VAC

Operating Data

Unit Capacity....10.2 m³/h ACMH at 500mbar abs (50% vacuum)
Inrush Current.....30A
Absorbed Power.....Max. 2.1kW
Earth Leakage Current.....>3.5 mA to PE
Lifting Height.....Max. allowed lifting height/pressure on
the discharge side 3m/0.3bar

Patents & Trademarks

FlexilooFirst™ is protected by Patent. Flexiloo® & FlexilooFirst™ are trademarks and/or registered trademarks of Flexiloo LLP. JETS™, CVS™ & Vacuumator® are trademarks and/or registered trademarks of Jets Vacuum AS.
© Copyright 2017, Flexiloo LLP

Warranty

All products of the company are sold and all services of the company are offered subject to Flexiloo LLP General Conditions of Sale , copies of which will be furnished upon request. The information provided herein is for guidance only; it does not constitute a guarantee of performance or specification of any individual product or component.